According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

Version 1.6	Revision Date: 07/13/2019	SDS Number: 800001005834					
SECTION	SECTION 1. IDENTIFICATION						
Produ	uct name	: Shell Morlina S	S2 B 320				
Produ	uct code	: 001D7812	: 001D7812				
Manu	ufacturer or supplier'	s details					
Manu	lfacturer/Supplier	: Shell Oil Proc PO Box 4427 Houston TX 7 USA					
	Request omer Service	: (+1) 877-276-7 :	7285				
Eme i Spill Healt	r gency telephone nu Information h Information	mber : 877-504-9351 : 877-242-7400					
	mmended use of the mmended use		ctions on use				

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements Hazard pictograms	:	No Hazard Symbol required
Signal word	:	No signal word
Hazard statements	:	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	:	Prevention: No precautionary phrases.
		Response:
		No precautionary phrases.
		Storage:
		Storage: No precautionary phrases.
		-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

Version	Revision Date:	SDS Number:
1.6	07/13/2019	800001005834

Print Date: 07/16/2019 Date of last issue: 08/27/2018

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

:

Chemical nature

Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346.

* contains one or more of the following CAS-numbers: 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-9.

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *		Not Assigned	0 - 90
N-phenyl-1- naphthylamine	N-1- naphthylaniline	90-30-2	< 0.99
(4- nonylphenoxy)acetic acid	(4- nonylphe- noxy)acetic acid	3115-49-9	< 0.099

SECTION 4. FIRST-AID MEASURES

If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms	:	Oil acne/folliculitis signs and symptoms may include formation

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

Version 1.6	Revision Date: 07/13/2019		DS Number: 00001005834	Print Date: 07/16/2019 Date of last issue: 08/27/2018
and e delay	ffects, both acute and ed			and spots on the skin of exposed areas. sult in nausea, vomiting and/or diarrhoea.
Protection of first-aiders		:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.	
medic	ation of any immediate cal attention and special nent needed		Treat symptomati	cally.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Avoid contact with skin and eyes.
Environmental precautions :	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
	Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for : containment and cleaning up	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

Version 1.6	Revision Date: 07/13/2019	SDS Number: 800001005834	Print Date: 07/16/2019 Date of last issue: 08/27/2018
		Soak up residu	directly or in an absorbent. we with an absorbent such as clay, sand or other al and dispose of properly.
Additional advice		see Chapter 8	n selection of personal protective equipment of this Safety Data Sheet. In disposal of spilled material see Chapter 13 of a Sheet.
SECTION	7. HANDLING AND S	STORAGE	

Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk as- sessment of local circumstances to help determine appropri- ate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Further information on stor- age stability	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
		Store at ambient temperature.
Packaging material	:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	:	Polyethylene containers should not be exposed to high tem- peratures because of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

Version	Revision Date:	SDS Number:
1.6	07/13/2019	800001005834

Print Date: 07/16/2019 Date of last issue: 08/27/2018

Oil m	nist, mineral	TWA (Inhal-	5 ma/m3	ACGIH
	,	able fraction)	- 5	
		abic fraction)		

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures :	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
	 General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

Version	Revision Date:
1.6	07/13/2019

SDS Number: 800001005834

Print Date: 07/16/2019 Date of last issue: 08/27/2018

Personal protective equipment

Respiratory protection	:	No respiratory protection is ordinarily required under normal conditions of use.
		In accordance with good industrial hygiene practices, precau- tions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentra- tions to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the spe- cific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appro- priate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].
Hand protection		Where hand contact with the product may accur the use of
Remarks	:	Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with break-through time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.
Eye protection	:	If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
Skin and body protection	:	Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.
Protective measures	:	Personal protective equipment (PPE) should meet recom- mended national standards. Check with PPE suppliers.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

Version 1.6	Revision Date: 07/13/2019	SDS Number: 800001005834	Print Date: 07/16/2019 Date of last issue: 08/27/2018
Therr	nal hazards	: Not applicable	
Envir	ronmental exposure	controls	
General advice		vant environme of the environm necessary, prev charged to was municipal or inc discharge to su Local guidelines	te measures to fulfill the requirements of rele- ntal protection legislation. Avoid contamination ent by following advice given in Section 6. If rent undissolved material from being dis- te water. Waste water should be treated in a ustrial waste water treatment plant before face water. s on emission limits for volatile substances ed for the discharge of exhaust air containing

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Liquid at room temperature.
Colour	:	amber
Odour	:	Slight hydrocarbon
Odour Threshold	:	Data not available
рН	:	Not applicable
pour point	:	-12 °C / 10 °F Method: ISO 3016
Initial boiling point and boiling range	:	> 280 °C / 536 °F estimated value(s)
Flash point	:	282 °C / 540 °F
		Method: ISO 2592
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available
Upper explosion limit / upper flammability limit	:	Typical 10 %(V)
Lower explosion limit / Lower flammability limit	:	Typical 1 %(V)
Vapour pressure	:	< 0.5 Pa (20 °C / 68 °F)
		estimated value(s)
Relative vapour density	:	> 1 estimated value(s)

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

Vers 1.6	sion	Revision Date: 07/13/2019		S Number: 0001005834	Print Date: 07/16/2019 Date of last issue: 08/27/2018
	Relativ	e density	:	0.897 (15 °C / 59	°F)
	Density	/	:	897 kg/m3 (15.0 Method: ISO 121	
	Solubili Wat	ity(ies) ter solubility	:	negligible	
	Solu	ubility in other solvents	:	Data not availabl	e
	Partitio octano	n coefficient: n- I/water	:	log Pow: > 6 (based on inform	ation on similar products)
	Auto-ig	nition temperature	:	> 320 °C / 608 °F	
		position temperature	:	Data not availabl	e
	Viscosi Visc	ty cosity, dynamic	:	Data not availabl	e
	Viso	cosity, kinematic	:	320 mm2/s (40.0	°C / 104.0 °F)
				Method: ASTM D	445
				25 mm2/s (100 °	C / 212 °F)
				Method: ASTM D	445
	Explos	ive properties	:	Not classified	
	Oxidizi	ng properties	:	Data not availabl	e
	Condu	ctivity	:	This material is n	ot expected to be a static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reac- tions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

Version 1.6	Revision Date: 07/13/2019	SDS Number: 800001005834	Print Date: 07/16/2019 Date of last issue: 08/27/2018
Basis	for assessment	the toxicology the data prese	ren is based on data on the components and of similar products.Unless indicated otherwise, nted is representative of the product as a han for individual component(s).
Skin	mation on likely route and eye contact are the ental ingestion.	-	posure although exposure may occur following
Acut	e toxicity		
<u>Prod</u>	uct:		
Acute	e oral toxicity	: LD50 (rat): > 5 Remarks: Low Based on avai	
Acute	inhalation toxicity	: Remarks: Base are not met.	ed on available data, the classification criteria
Acute	e dermal toxicity	: LD50 (Rabbit): Remarks: Low Based on avai	

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Components:

N-phenyl-1-naphthylamine:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Remarks: Classified Skin Sensitiser Category 1B.

(4-nonylphenoxy)acetic acid:

Remarks: May cause an allergic skin reaction in sensitive individuals.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

Version	Revision Date:	SDS Number:	Print Date: 07/16/2019
1.6	07/13/2019	800001005834	Date of last issue: 08/27/2018

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

1

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

Version	Revision Date:
1.6	07/13/2019

SDS Number: 800001005834 Print Date: 07/16/2019 Date of last issue: 08/27/2018

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	:	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Ecotoxicity		
<u>Product:</u> Toxicity to fish (Acute toxici- ty)	:	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to daphnia and other aquatic invertebrates (Acute toxicity)	:	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to algae (Acute tox- icity)	:	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to fish (Chronic tox- icity)	:	Remarks: Data not available
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	Remarks: Data not available
Toxicity to microorganisms (Acute toxicity)	:	Remarks: Data not available

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

rsion	Revision Date: 07/13/2019		0S Number: 0001005834	Print Date: 07/16/2019 Date of last issue: 08/27/2018
Com	oonents:			
-	enyl-1-naphthylamine: ctor (Acute aquatic tox-	:	1	
Persi	stence and degradabil	ity		
Produ	uct:			
	gradability	:	Major constituent	idily biodegradable. s are inherently biodegradable, but contains may persist in the environment.
Bioad	cumulative potential			
<u>Prod</u>	<u>uct:</u>			
Bioac	cumulation	:	Remarks: Contain cumulate.	ns components with the potential to bioac-
Mobi	ity in soil			
Produ	<u>uct:</u>			
Mobili	ity	:		under most environmental conditions. will adsorb to soil particles and will not be
			Remarks: Floats	on water.
Other	adverse effects			
Produ	uct:			
Additi matio	onal ecological infor- n	:	ozone creation po Product is a mixto	one depletion potential, photochemical otential or global warming potential. ure of non-volatile components, which will n in any significant quantities under normal
			Poorly soluble mi Causes physical	xture. fouling of aquatic organisms.
				ot cause chronic toxicity to aquatic organ- tions less than 1 mg/l.

Disposal methods

Waste from residues	:	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth- ods in compliance with applicable regulations.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

Version 1.6	Revision Date: 07/13/2019	SDS Number: 800001005834	Print Date: 07/16/2019 Date of last issue: 08/27/2018
		Do not dispose i courses	nto the environment, in drains or in water
		ground water, or	hould not be allowed to contaminate soil or be disposed of into the environment. used product is dangerous waste.
Conta	minated packaging	to a recognized the collector or c Disposal should	rdance with prevailing regulations, preferably collector or contractor. The competence of contractor should be established beforehand. be in accordance with applicable regional, al laws and regulations.
Local Rema	legislation rks	•	be in accordance with applicable regional, al laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Naphthalene	91-20-3	100	*

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

Version	Revision Date:	SDS Number:	Print Date: 07/16/2019
1.6	07/13/2019	800001005834	Date of last issue: 08/27/2018

*: Calculated RQ exceeds reasonably attainable upper limit., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA., The components with RQs are given for information.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	No SARA Hazards
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Naphthalene 91-20-3 0.0001 %

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy naphthenic; 64742-52-5 Baseoil -unspecified

California Prop. 65

WARNING: This product can expose you to chemicals including Naphthalene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.
DSL	:	All components listed.

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

Version	Revision Date:	SDS Number:	Print Date: 07/16/2019
1.6	07/13/2019	800001005834	Date of last issue: 08/27/2018
OSHA Z-1		its for Air Conta	eighted average
ACGIH / TWA		8-hour, time-we	ighted average
OSHA Z-1 / TWA		8-hour time we	Ibbreviations and acronyms used in this docu-
Abbreviations and Acronyms		The standard a	oked up in reference literature (e.g. scientific
		Hygienists ADR = Europea Carriage of Da AICS = Austral ASTM = Ameri BEL = Biologic BTEX = Benze CAS = Chemic CEFIC = Europ CLP = Classific COC = Clevela DIN = Deutsch DMEL = Derive DNEL = Derive DNEL = Derive DNEL = Canada EC = Europear EC50 = Effectiv ECETOC = Eu gy Of Chemica ECHA = Europ EINECS = The Chemical Subs EL50 = Effectiv ENCS = Japan Inventory EWC = Europear GHS = Globally Labelling of Ch IARC = Internar IC50 = Inhibitor IMDG = Internar INV = Chinese IP346 = Institut determination of KECI = Korea I LC50 = Lethal LL/EL/IL = Leth LS0 = Lethal I MARPOL = Internar NOEC/NOEL = served Effect L	es Institut fur Normung ed Minimal Effect Level d No Effect Level Domestic Substance List n Commission ve Concentration fifty ropean Center on Ecotoxicology and Toxicolo- ls ean Chemicals Agency European Inventory of Existing Commercial stances ve Loading fifty ese Existing and New Chemical Substances van Waste Code y Harmonised System of Classification and emicals tional Agency for Research on Cancer tional Agency for Research on Cancer tional Air Transport Association ry Concentration fifty y Level fifty ational Maritime Dangerous Goods Chemicals Inventory te of Petroleum test method N° 346 for the of polycyclic aromatics DMSO-extractables Existing Chemicals Inventory Concentration fifty Dose fifty per cent. nal Loading/Effective Loading/Inhibitory loading Loading fifty ernational Convention for the Prevention of Ships No Observed Effect Concentration / No Ob-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Morlina S2 B 320

Versio 1.6	on Revision Date: 07/13/2019	SDS Number: 800001005834	Print Date: 07/16/2019 Date of last issue: 08/27/2018
		PICCS = Philip Substances PNEC = Predic REACH = Regi Chemicals RID = Regulatio gerous Goods I SKIN_DES = S STEL = Short to TRA = Targete TSCA = US To TWA = Time-W	nt, Bioaccumulative and Toxic pine Inventory of Chemicals and Chemical ted No Effect Concentration stration Evaluation And Authorisation Of ons Relating to International Carriage of Dan- by Rail kin Designation erm exposure limit d Risk Assessment xic Substances Control Act Veighted Average ersistent and very Bioaccumulative
A	vertical bar () in the left ma	rgin indicates an am	endment from the previous version.
	ources of key data used to ompile the Safety Data		a are from, but not limited to, one or more mation (e.g. toxicological data from Shell

compile the Safety Data Sheet	•	sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).
Revision Date	:	07/13/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN