According to EC No 1907/2006 as amended as at the date of this SDS

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

: Shell Tellus S3 V 32 Trade name

Product code : 001D7762

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Transmission oil.

Substance/Mixture

Uses advised against

This product must not be used in applications other than those

listed in Section 1 without first seeking the advice of the

supplier.

### 1.3 Details of the supplier of the safety data sheet

: Société des Pétroles Shell Manufacturer/Supplier

Tour Pacific

11/13 cours Valmy - La Défense 7 F-92977 PARIS LA DEFENSE

Telephone : (+33) 0969366018 Telefax (+33) 0969366030

**Email Contact for Safety Data** : If you have any enquiries about the content of this SDS

Sheet please email lubricantSDS@shell.com

1.4 Emergency telephone number

: Shell (en France 24/24h): 0800 33 86 86 (+33 4 82 90 75 50)

ORFILA (INRS): + 33 (0)1 45 42 59 59

#### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, H412: Harmful to aquatic life with long lasting

Category 3 effects.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms No Hazard Symbol required

Signal word No signal word

PHYSICAL HAZARDS: Hazard statements

Not classified as a physical hazard

according to CLP criteria.

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

**HEALTH HAZARDS:** 

Not classified as a health hazard under CLP

criteria.

**ENVIRONMENTAL HAZARDS:** 

H412 Harmful to aquatic life with long lasting

effects.

Precautionary statements : Prevention:

P273 Avoid release to the environment.

Response:

No precautionary phrases.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents/ container to an

approved waste disposal plant.

#### 2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

### **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

Chemical nature : Highly refined mineral oils and additives.

The highly refined mineral oil contains <3% (w/w) DMSO-

extract, according to IP346.

: \* contains one or more of the following CAS-numbers

(REACH registration numbers): 64742-53-6 (01-2119480375-

34), 64742-54-7 (01-2119484627-25), 64742-55-8 (01-2119487077-29), 64742-56-9 (01-2119480132-48), 64742-65-

0 (01-2119471299-27), 68037-01-4 (01-2119486452-34), 72623-86-0 (01-2119474878-16), 72623-87-1 (01-

2119474889-13), 8042-47-5 (01-2119487078-27), 848301-69-

9 (01-0000020163-82).

#### **Hazardous components**

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(REGULATION	[%]
	Registration	(EC) No	
	number	1272/2008)	
Phenol, isopropylated,	68937-41-7	Repr.2; H361f	0,25 - 0,9
phosphate (3:1)	273-066-3	STOT RE2: H373	

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

[Triphenyl phosphate > 5%]	01-2119535109-41	Aquatic Acute1; H401 Aquatic Chronic1; H410	
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *		Asp. Tox.1; H304	0 - 90

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with

water and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If persistent irritation occurs, obtain medical attention.

If swallowed : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Oil acne/folliculitis signs and symptoms may include formation

of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Notes to doctor/physician:

Treat symptomatically.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon

dioxide, sand or earth may be used for small fires only.

3 / 23 800001007577 FR

According to EC No 1907/2006 as amended as at the date of this SDS

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

Unsuitable extinguishing

media

: Do not use water in a jet.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

 Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.

# 5.3 Advice for firefighters

Special protective equipment

for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : 6.1.1 For non emergency personnel:

Avoid contact with skin and eyes. 6.1.2 For emergency responders: Avoid contact with skin and eyes.

#### 6.2 Environmental precautions

Environmental precautions : Use appropriate containment to avoid environmental

contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate

barriers.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Slippery when spilt. Avoid accidents, clean up immediately.

Prevent from spreading by making a barrier with sand, earth

or other containment material.

Reclaim liquid directly or in an absorbent.

Soak up residue with an absorbent such as clay, sand or other

suitable material and dispose of properly.

#### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

# **SECTION 7: Handling and storage**

**General Precautions** : Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid prolonged or repeated contact with skin.

Avoid inhaling vapour and/or mists.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning

materials in order to prevent fires.

**Product Transfer** : Proper grounding and bonding procedures should be used

during all bulk transfer operations to avoid static accumulation.

#### 7.2 Conditions for safe storage, including any incompatibilities

Other data : Keep container tightly closed and in a cool, well-ventilated

place. Use properly labeled and closable containers.

Store at ambient temperature.

Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

Packaging material : Suitable material: For containers or container linings, use mild

steel or high density polyethylene.

Unsuitable material: PVC.

Container Advice : Polyethylene containers should not be exposed to high

temperatures because of possible risk of distortion.

7.3 Specific end use(s)

Specific use(s) : Not applicable

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parameters	Basis
------------	---------	------------------	--------------------	-------

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

	of exposure)		
Oil mist, mineral	TWA	5 mg/m3	US. ACGIH Threshold Limit Values

#### **Biological occupational exposure limits**

No biological limit allocated.

### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

#### 8.2 Exposure controls

**Engineering measures**The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

#### General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

#### Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended. Approved to EU Standard EN166.

Hand protection

Remarks

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Skin and body protection

: Skin protection is not ordinarily required beyond standard work clothes.

It is good practice to wear chemical resistant gloves.

Respiratory protection

: No respiratory protection is ordinarily required under normal conditions of use.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.

If engineering controls do not maintain airborne

concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

#### SAFFTY DATA SHFFT

According to EC No 1907/2006 as amended as at the date of this SDS

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

> Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)]

meeting EN14387 and EN143.

Thermal hazards : Not applicable

### **Environmental exposure controls**

General advice : Take appropriate measures to fulfill the requirements of

relevant environmental protection legislation. Avoid

contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant

before discharge to surface water.

Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing

vapour.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Appearance : Liquid at room temperature.

Colour : amber

Odour : Slight hydrocarbon Odour Threshold : Data not available рH : Not applicable

: -39 °CMethod: ISO 3016 pour point

Initial boiling point and boiling : > 280 °Cestimated value(s)

range

: 200 °C Flash point

Method: ISO 2592

**Evaporation rate** : Data not available Flammability (solid, gas) : Data not available

Upper explosion limit : Typical 10 %(V)

Lower explosion limit : Typical 1 %(V)

According to EC No 1907/2006 as amended as at the date of this SDS

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

: < 0,5 Pa (20 °C) Vapour pressure

estimated value(s)

Relative vapour density : > 1estimated value(s)

: 0,862 (15,0 °C) Relative density

Density : 862 kg/m3 (15,0 °C)

Method: ISO 12185

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : Data not available

Partition coefficient: n-

octanol/water

: log Pow: > 6(based on information on similar products)

Auto-ignition temperature

320 °C

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available Viscosity, kinematic

: 32 mm2/s (40,0 °C) Method: ASTM D445

6,5 mm2/s (100 °C) Method: ASTM D445

1000 mm2/s (-20 °C) Method: ASTM D445

Explosive properties : Not classified

Oxidizing properties : Data not available

9.2 Other information

Conductivity : This material is not expected to be a static accumulator.

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following

#### SAFFTY DATA SHFFT

According to EC No 1907/2006 as amended as at the date of this SDS

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

sub-paragraph.

### 10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

# 10.6 Hazardous decomposition products

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

### **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

: Information given is based on data on the components and Basis for assessment

> the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a

whole, rather than for individual component(s).

exposure

Information on likely routes of : Skin and eye contact are the primary routes of exposure

although exposure may occur following accidental ingestion.

### **Acute toxicity**

**Product:** 

Acute oral toxicity : LD50 rat: > 5.000 mg/kg

Remarks: Low toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : LD50 Rabbit: > 5.000 mg/kg

Remarks: Low toxicity:

Based on available data, the classification criteria are not met.

### Skin corrosion/irritation

#### Product:

According to EC No 1907/2006 as amended as at the date of this SDS

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

### Serious eye damage/eye irritation

### **Product:**

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met

### Respiratory or skin sensitisation

#### **Product:**

Remarks: For respiratory and skin sensitisation:, Not a sensitiser., Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

### **Product:**

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

#### Carcinogenicity

#### **Product:**

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

### Reproductive toxicity

# **Product:**

Remarks: Suspected of damaging fertility., Not a developmental toxicant., Based on available data, the

classification criteria are not met.

#### STOT - single exposure

According to EC No 1907/2006 as amended as at the date of this SDS

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

#### **Product:**

Remarks: Based on available data, the classification criteria are not met.

#### STOT - repeated exposure

#### **Product:**

Remarks: Based on available data, the classification criteria are not met.

### **Aspiration toxicity**

#### **Product:**

Not an aspiration hazard.

#### **Further information**

#### **Product:**

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

### Summary on evaluation of the CMR properties

Germ cell mutagenicity-

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity -

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

Reproductive toxicity -

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Basis for assessment : Ecotoxicological data have not been determined specifically

for this product.

Information given is based on a knowledge of the components

and the ecotoxicology of similar products.

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test

extract).

**Product:** 

Toxicity to fish (Acute

toxicity)

: Remarks: LL/EL/IL50 10-100 mg/l

Harmful

Toxicity to crustacean (Acute

toxicity)

: Remarks: LL/EL/IL50 10-100 mg/l

Harmful

Toxicity to algae/aquatic plants (Acute toxicity)

: Remarks: LL/EL/IL50 10-100 mg/l

Harmful

Toxicity to fish (Chronic

toxicity)

: Remarks: Data not available: Remarks: Data not available

Toxicity to crustacean

(Chronic toxicity)

Toxicity to microorganisms

(Acute toxicity)

Remarks: Data not available

#### 12.2 Persistence and degradability

**Product:** 

Biodegradability : Remarks: Not readily biodegradable., Major constituents are

inherently biodegradable, but contains components that may

persist in the environment.

12.3 Bioaccumulative potential

**Product:** 

Bioaccumulation : Remarks: Contains components with the potential to

bioaccumulate.

Partition coefficient: n-

octanol/water

: log Pow: > 6Remarks: (based on information on similar

products)

12.4 Mobility in soil

**Product:** 

Mobility : Remarks: Liquid under most environmental conditions., If it

enters soil, it will adsorb to soil particles and will not be

mobile.

Remarks: Floats on water.

12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This mixture does not contain any REACH registered

13 / 23 800001007577 FR

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

substances that are assessed to be a PBT or a vPvB.

#### 12.6 Other adverse effects

#### **Product:**

Additional ecological

information

: Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential., Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use.

Poorly soluble mixture., Causes physical fouling of aquatic

organisms.

Mineral oil does not cause chronic toxicity to aquatic organisms at concentrations less than 1 mg/l.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water

courses

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably

to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local legislation

Waste catalogue :

EU Waste Disposal Code (EWC):

Waste Code :

13 02 05\*

Remarks : Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

Classification of waste is always the responsibility of the end user.

### **SECTION 14: Transport information**

14.1 UN number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 Proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good CDNI Inland Water Waste : NST 3411 Mineral Lubricating Oils

Agreement

ADR : Not regulated as a dangerous good RID : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.5 Environmental hazards

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

**Additional Information**: ADN - Classified ID9006 only when carried in tank vessels.

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation

. 36

(Annex XIV)

: Product is not subject to Authorisation under REACH.

Occupational Illnesses (R-

461-3, France)

Volatile organic compounds : 0 %

Other regulations

: The following regulatory information is not intended to be comprehensive and does not exempt the end user of the product to refer to all official documents to determine its obligations.

According type of product and quantity stored, check for applicability of Code of environment: art. R511-9 - Nomenclature of classified facilities.

Labour code: Exposure forbidden to certain works/products to

- Young people under 16 years old : art. D4153-25

- Young people under 18 years old : art. D4153-26, D4153-27

- Pregnant or breast-feeding women : art. D4152-10, D4152-11

- Fixed term-contract or temporary staff: art. D4154-1, D4154-2

Social security code - Article L.461-6, Appendix A, no. 601-15. Labour code - Intensified medical supervision: Articles R.4624-18 and R.4624-19, decree 2012-135 of 30.01.2012.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), annex XIV.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), annex XVII.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances (Seveso III).

Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work and its amendments.

Directive 1994/33/EC on the protection of young people at work and its amendments.

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

pregnant workers and workers who have recently given birth or are breastfeeding and its amendments.

#### The components of this product are reported in the following inventories:

EINECS : All components listed or polymer exempt.

TSCA : All components listed.

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

#### **SECTION 16: Other information**

### REGULATION (EC) No 1272/2008 Classification procedure:

Long-term (chronic) aquatic hazard, Expert judgement and weight of evidence

Category 3, H412 determination.

#### **Full text of H-Statements**

H304 May be fatal if swallowed and enters airways.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H401 Toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Acute Short-term (acute) aquatic hazard Aquatic Chronic Long-term (chronic) aquatic hazard

Asp. Tox. Aspiration hazard Repr. Reproductive toxicity

STOT RE Specific target organ toxicity - repeated exposure

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this

document can be looked up in reference literature (e.g.

scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

### Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and

Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

**Chemical Substances** 

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances

Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the

determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of

Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No

Observed Effect Level

OE\_HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical

Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of

Chemicals

RID = Regulations Relating to International Carriage of

Dangerous Goods by Rail

SKIN DES = Skin Designation

STEL = Short term exposure limit

TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

#### **Further information**

Training advice : Provide adequate information, instruction and training for

operators.

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

Other information : A vertical bar (I) in the left margin indicates an amendment

from the previous version.

Sources of key data used to compile the Safety Data

Sheet

: The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

# Identified Uses according to the Use Descriptor System

**Uses - Worker** 

Title : General use of lubricants and greases in vehicles or

machinery.- Industrial

**Uses - Worker** 

Title : General use of lubricants and greases in vehicles or

machinery .- Professional

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

19 / 23 800001007577 FD

# Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

**Exposure Scenario - Worker** 

Exposure Scenario - Worke	·
30000010660	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or machinery Industrial
Use Descriptor	Sector of Use: SU 3 Process Categories: PROC 1, PROC 2, PROC 8b, PROC 9 Environmental Release Categories: ERC4, ERC7, ATIEL- ATC SPERC 4.Bi.v1
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for human health.

Section 2.1	Control of Worker Exposure
Product Characteristics	

Contributing Scenarios	Risk Management Measures
------------------------	--------------------------

Section 2.2	Control of Environmental Exposure	
Amounts Used		
EU tonnage (tonnes per year):		2.631,1
Fraction of EU tonnage used	in region:	0,1
Fraction of Regional tonnage	used locally:	0,1
Frequency and Duration of	Use	
Emission Days (days/year):		300
Environmental factors not	influenced by risk management	
Local freshwater dilution fact	or:	10
Local marine water dilution factor:		100
Other Operational Conditio	ns affecting Environmental Exposure	<b>,</b>
	ons as process operates without water	
contact.		
	rocess (after typical onsite RMMs):	5,00E-05
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant):		2,00E-11
Release fraction to soil from process (after typical onsite RMMs):		0
Technical conditions and n	neasures at process level (source) to	prevent release
Common practices vary acros	ss sites thus conservative process	
release estimates used.		
Technical onsite conditions	s and measures to reduce or limit dis	charges, air
emissions and releases to	soil	
Treat air emission to provide	a typical removal efficiency of (%)	70

# Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

Prevent discharge of undissolved substance to or recover from onsite	
wastewater.	
User sites are assumed to be provided with oil/water separators or	
equivalent and for waste water to be discharged via public sewer	
system.	
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	lant
Estimated substance removal from wastewater via domestic sewage	0,1
treatment (%)	
Assumed domestic sewage treatment plant flow (m3/d)	2,00E+03
Maximum allowable site quantity (MSafe) based on OCs and RMMs	263.432,1
as above (kg/day):	
Conditions and Measures related to external treatment of waste fo	r disposal
External treatment and disposal of waste should comply with applicable	local and/or regional
regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable	local and/or regional
regulations.	

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
No exposure assessment presented for human health.		

# Section 3.2 - Environment

Used ECETOC TRA model.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

#### **Section 4.2 - Environment**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a sitespecific chemical safety assessment is required.

For further information see www.ATIEL.org/REACH\_GES.

# Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

**Exposure Scenario - Worker** 

Exposure occitatio - Worke	•
300000010661	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or
	machinery Professional
Use Descriptor	Sector of Use: SU 22
	Process Categories: PROC1, PROC2, PROC8a, PROC8b,
	PROC20
	Environmental Release Categories: ERC9a, ERC9b,
	ESVOC SpERC 9.6b.v1
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of
	containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for human health.

Section 2.1	Control of Worker Exposure
Product Characteristics	

	1
Contributing Scenarios	Risk Management Measures
Continuating Cochanos	Trior management measures

Section 2.2	Control of Environmental Exposur	re
Amounts Used		
EU tonnage (tonnes per year):		5.387,2
Fraction of EU tonnage used	in region:	0,1
Fraction of Regional tonnage	used locally:	0,1
Frequency and Duration of	Use	
Emission Days (days/year):		365
Environmental factors not i	nfluenced by risk management	
Local freshwater dilution factor	or:	10
Local marine water dilution factor:		100
Other Operational Condition	ns affecting Environmental Exposu	re
Negligible wastewater emissions as process operates without water		r
contact.		
Release fraction to air from pr	ocess (after typical onsite RMMs):	
Release fraction to wastewater from process (after typical onsite		5,00E-04
RMMs and before (municipal)	sewage treatment plant):	
Release fraction to soil from p	process (after typical onsite RMMs):	1E-03
Technical conditions and m	easures at process level (source) t	o prevent release
Common practices vary acros	ss sites thus conservative process	
release estimates used.		
Technical onsite conditions and measures to reduce or limit discharges, air		
emissions and releases to s	soil	

# Shell Tellus S3 V 32

Version 2.2 Revision Date 28.05.2019 Print Date 29.05.2019

	T	
Prevent discharge of undissolved substance to or recover from onsite		
wastewater.		
Organisational measures to prevent/limit release from site		
Do not apply industrial sludge to natural soils.		
Sludge should be incinerated, contained or reclaimed.		
Conditions and Measures related to municipal sewage treatment pl	lant	
Estimated substance removal from wastewater via domestic sewage	0,1	
treatment (%)		
Assumed domestic sewage treatment plant flow (m3/d)	2,00E+03	
Maximum allowable site quantity (MSafe) based on OCs and RMMs	2.972,7	
as above (kg/day):		
Conditions and Measures related to external treatment of waste for	r disposal	
External treatment and disposal of waste should comply with applicable	local and/or regional	
regulations.		
Conditions and measures related to external recovery of waste		
External recovery and recycling of waste should comply with applicable local and/or regional		
regulations.		

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment	
Used ECETOC TRA model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

# **Section 4.2 - Environment**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a sitespecific chemical safety assessment is required.

For further information see www.ATIEL.org/REACH\_GES.